

BENEFITS

- Safe composition, better for you, better for nature
- A trendy product for new possibilities
- 4 different thicknesses
- 0.4 mm (1/64") as thin as paper, for flexible applications

APPLICATIONS

Interior signage, Architectural models, decoration, gifts, promotional items, personalized cards, DIY projects.

SPECIFICATIONS


Finish	Matte
Composition	Natural plywood
Engraving depth	0.1 mm (.004")
Full sheet	610 x 305mm (24" x 12")
Half sheet	-
Quarter sheet	-
Other size	-

CAPABILITIES

Interior	■
Exterior	-
Shear	0.4mm (1/64") & 1.0mm (3/64) ■
Saw	2.5mm (3/32") & 4.5mm (11/64) ■
Silk screen	■
Hot stamp	-
Heat bending	-
Scratch resistant	-
Flexible	■
Break resistant	-
UV resistant	■
Min. temp.	-200°C (-328°F)
Max. temp.	100°C (212°F)

TECH TIPS

We recommend that you let the material acclimate to interior conditions before use.
 Apply masking paper (ref. 45897) to the sheet to avoid dust and fumes during CO₂ laser cutting.
 Hold the sheet flat on the honeycomb table using clamps (ref. 83366).



Double-sided

wood species

birch	82741	0.4 mm (1/64")	82742	1.0 mm (3/64")	82743	2.5 mm (3/32")	82744	4.5 mm (11/64")
beech			82747		82748			
oak			82745		82746			
walnut			82749		82750			

Wood is a natural organic material. Thickness, color and aspect can vary from one sheet to another.

Packaged by 5



Masking paper ref. 45897



Clamps (pack of 6) ref. 83366



Printed colors for indication only. Cannot serve as a substitute for real material sample. Laserwood-GV_US_V1-0_0919.

