

BENEFITS

- Laser engraving and cutting
- Glossy or frosted finish
- Excellent for clear signage
- Laser and rotary engravable
- Interior and exterior use



APPLICATIONS

Interior and exterior signage applications

SPECIFICATIONS

Finish	Glossy
Composition	Acrylic
Engraving depth	0.25 mm (0.010")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	0.5 mm (0.020")
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	-
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (180°F)

TECH TIPS

Acrylic sheets can be engraved, paint filled, or used for cutouts. Another common use is to simply add thickness to an engraved sheet of metal or plastic. The added thickness has a strong presence on the wall - especially helpful if the sign is not framed.

Opaque

white	83440	3 mm (1/8")	6 mm (.20")
opaque black	83443		

Clear

clear	83423	3 mm (1/8")	6 mm (.20")	10 mm (.20")
translucent green	83426			
translucent blue	83427			

Fluorescent

yellow	83428	3.2 mm (.125")
orange	83430	
pink	83429	

Frosted

frosted white	83431	3 mm (1/8")
frosted light blue	83434	
frosted sky blue	83438	
frosted blue ocean	83435	
frosted blue lagoon	83437	
frosted green	83436	
frosted yellow	83432	
frosted pink	83439	
frosted mauve	83433	



WATCH VIDEO HERE



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

