

BENEFITS

- High quality engraver's brass
- Paint fill with Gravotech recommended paint

APPLICATIONS

High quality signage, company name plates...

SPECIFICATIONS

Finish	Polished or Solid
Composition	Brass
Engraving Depth	.012"
Full Sheet	26" x 52"
Half Sheet	26" x 26" (add -H)
Quarter Sheet	13" x 26" (add -Q)
Other Size(s)	-

CAPABILITIES

Interior	■
Exterior	■
Shear	■
Saw	■
Screen Print	■
Hot Stamp	-
Heat bending	-
Scratch resistant	-
Flexible	-
Break resistant	■
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	370°C (700°F)

TECH TIPS

Clean your Gravobras[™] Exterior regularly to preserve its brightness or add a protective varnish after engraving.

You can use Gravotech recommended paint to colour any Gravobras[™] Exterior engraving. See p.77.



Rotary



UV Print



Indoor



Outdoor



Surface

Polished Brass

Surface / Engraving Colour

Polished Brass / Brass	22032 (.040")
	22034 (1/16")
	22036 (1/12")
	22038 (1/8")



Solid Brass

Surface / Engraving Colour

Solid Brass / Brass	22031 (.040")
	22033 (1/16")
	22035 (1/12")
	22037 (1/8")

Solid brass is unpolished and may feature surface defects.

