

BENEFITS

- UV stable
- Excellent for interior and exterior signage
- A wide range of colors
- Matte finish
- Microthin surface layer for detailed engraving
- Reduce inventory with one material for rotary, laser, indoor and outdoor needs

APPLICATIONS

Architectural signage, industrial signage, labelling, legend plates...

SPECIFICATIONS

Finish	Matte
Composition	Acrylic
Engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	■
Saw	-
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	-
Flexible	■
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

The most versatile plastic material: indoor, outdoor, laser and rotary engraving and cutting. One product, one stock, many applications.

You can mix any surface and any core colors on demand.

For custom colors, see Custom materials on demand p.10.



Flexibility and performance for indoor and outdoor applications

Double-sided	2-ply			surface / core color	2-ply	surface / core color
	0.5 mm (.020")	0.8 mm (1/32")	1.3 mm (.050")			
Matte						
white / red	51047	51006	70005	burgundy / white	51043	49997
white / blue	51057	51011	80763	burgundy / gold	51062	51016
white / black	51017	49971	69991	purple / white	67005*	67006*
almond / black	51022	49978	80764		80771*	
yellow / red	51048	51007	70006			
yellow / blue	51058	51012	80765			
yellow / black	51018	49973	69992			
dark yellow / black	51019	49977	80766			
orange / white	51035	51005	80767			
orange / black	51020	51001	80768			
red / white	51034	49988	69995		78586**	
red / black			81585**			
red / yellow	51055	51009	80769			
red / gold	72304**					

*Subject to premature colorfading
** Sold in North America Only



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

