

BENEFITS

- Interior use
- Profile available with or without adhesive backing



APPLICATIONS

DDA & ADA compliant, tactile signage

SPECIFICATIONS

Finish	Matte
Composition	ABS
Engraving depth	-
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	-
Shear	■
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	■
Break resistant	■
UV resistant	-
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

Matte finish and wide range of colors ideal for your Braille and tactile signs and pictograms. Americans with Disabilities Act (ADA) compliant. For better visibility, choose contrasted colors.

	1-ply		1-ply	
	0.8 mm (1/32")	1.6 mm (1/16")	0.8 mm (1/32")	1.6 mm (1/16")
clear	32729		69712	31360
bright white	37042	29879	37050	31410
white	37033	29880	69713	32185
almond	37070	29882	37065	32276
yellow	24998	29883	37037	31256
rust	32291	29884	29902	
red	25001	29885	29901	
burgundy	69711	29888	31256	
tan	32726	29889		
taupe	37047	29890		
brown	31631	29891		
chocolate brown	37058	29892		
pine green	37060	29895		
metallic blue	37032	29896		
azure blue	37048	29897		

The Gravotac™ process :



Adhere 0.8 mm (1/32") profile material to 1.6 mm (1/16") or 3.2 mm (1/8") substrate. Engrave using outline font. Peel excess profile material off substrate.



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

