

BENEFITS

- Interior use
- Profile available with or without adhesive backing



Rotary UV Print Indoor

APPLICATIONS

DDA & ADA compliant, tactile signage

SPECIFICATIONS

Finish	Matte
Composition	ABS
Engraving depth	-
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	-
Shear	■
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	■
Break resistant	■
UV resistant	-
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

Matte finish and wide range of colors ideal for your Braille and tactile signs and pictograms. Americans with Disabilities Act (ADA) compliant. For better visibility, choose contrasted colors.

	1-ply		
	0.8 mm (1/32")	1.6 mm (1/16")	3.2 mm (1/8")
clear	32729		
bright white	37042	29879	31260
white	37033	29880	31236
almond	37070	29882	
yellow	24998		
red	25001	29885	
burgundy		29888	
taupe	37047	29890	31261
brown	31631		
chocolate brown	37058	29892	
metallic blue		29896	
azure blue	37048	29897	

	1-ply		
	0.8 mm (1/32")	1.6 mm (1/16")	3.2 mm (1/8")
navy blue	69712	29898	31360
candlewick	37050	29899	31410
silver grey	69713	29900	32185
slate	37065	29901	
black	37037	29902	31256

The Gravotac™ process :



Adhere 0.8 mm (1/32") profile material to 1.6 mm (1/16") or 3.2 mm (1/8") substrate. Engrave using outline font. Peel excess profile material off substrate.



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

