

BENEFITS

- Better for you, better for the environment
- A trendy product for new possibilities
- 4 different thicknesses
- 1/64" - as thin as paper, for flexible applications

APPLICATIONS

Interior signage, architectural models, decorations, gifts, promotional items, personalized cards, DIY projects...

SPECIFICATIONS

Finish	Matte
Composition	Natural Plywood
Engraving Depth	.004"
Full Sheet	12" x 24"
Half Sheet	-
Quarter Sheet	-
Other Size(s)	-

CAPABILITIES

Interior	■
Exterior	-
Shear	(1/64" & 3/64")
Saw	(3/32" & 11/64")
Screen Print	■
Hot Stamp	-
Heat bending	-
Scratch resistant	-
Flexible	■
Break resistant	-
UV resistant	■
Min. temp.	-200°C (-328°F)
Max. temp.	100°C (212°F)

TECH TIPS

We recommend that you let the material acclimate to interior conditions before use.

CO₂

Rotary



UV Print



Indoor



Surface

Matte (PACK OF 5)**

Surface

Birch	82741 (1/64")*
	82742 (3/64")*
	82743 (3/32")*
	82744 (11/64")*

Beach	82747 (3/32")*
	82748 (11/64")*

Oak	82745 (3/32")*
	82746 (11/64")*

Walnut	82749 (3/32")*
	82750 (11/64")*

Matte (PACK OF 1)

Surface

Birch	83935 (3/32")*
	83936 (11/64")*

Beach	83937 (3/32")*
	83938 (11/64")*

Oak	83939 (3/32")*
	83940 (11/64")*

Walnut	83941 (3/32")*
	83942 (11/64")*

* All Laser Wood is double sided & can be engraved on both sides.

** Packs of 5 cannot be mixed. One finish only.

Wood is a natural organic material. Thickness, colour and aspect can vary from one sheet to another.



Masking Paper 6"x 100 yds - 45897

Apply to sheet surface to protect it during CO₂ laser engraving & cutting.



Pack of 6 Clamps - 83366

Use to hold sheet flat on honeycomb table.

