

BENEFITS

- High quality engraver's brass
- Paint fill with Gravotech recommended paint



APPLICATIONS

High quality signage, company name plates

SPECIFICATIONS

Finish	Solid or shiny polished
Composition	Brass
Engraving depth	0.3 mm (.012")
Full sheet	1340 mm x 670 mm (52" x 26")
Half sheet	670 mm x 670 mm (26" x 26")
Quarter sheet	670 mm x 335 mm (26" x 13")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	■
Saw	■
Silk screen	■
Hot stamp	-
Heat bending	-
Scratch resistant	-
Flexible	-
Break resistant	■
UV resistant	-
Min. temp.	-40°C (-40°F)
Max. temp.	370°C (700°F)

TECH TIPS

Brass oxidation is a natural phenomenon. Clean your Gravobrasst™ Exterior regularly to preserve its brightness or add a protective varnish after engraving. Solid brass is unpolished and may feature surface defects.

You can use Gravotech recommended paint to color any Gravobrasst™ Exterior engraving. See p.67. Use of chemicals on this material is not recommended.

Shiny polished

shiny polished brass	22032	1.0 mm (.040")
	22034	1.5 mm (1/16")
	22036	2.0 mm (1/12")
	22038	3.0 mm (1/8")

Solid

solid brass	22031	1.0 mm (.040")
	22033	1.5 mm (1/16")
	22035	2.0 mm (1/12")
	22037	3.0 mm (1/8")

Solid brass is unpolished and may feature surface defects.



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

