	ACRYLIC			
ENGRAVING MATERIALS	CO <sub>2</sub> Rotary	UV Print Indoor	Outdoor Surface Subsurface	BE
Opaque		Frosted		
Surface Colour		Surface Colour		
White	<b>83440</b> (1/8″) <b>83441</b> (.20″)	White	<b>83431</b> (1/8″)	•
Black	<b>83442</b> (1/8″) <b>83443</b> (.20″)	Light Blue	<b>83434</b> (1/8″)	AF
		Sky Blue	83438 (1/8″)	Int ap
Clear		Blue Ocean	<b>83435</b> (1/8″)	SP
Surface Colour Clear	<b>83423</b> (1/8") <b>83424</b> (.20") <b>83425</b> (.40")	Blue Lagoon	<b>83437</b> (1/8″)	Co En Fu Ha
Translucent Green	<b>83426</b> (1/8")	Green	<b>83436</b> (1/8″)	Qu Otl
Translucent Blue	<b>83427</b> (1/8")	Yellow	<b>83432</b> (1/8″)	CA
		Pink	<b>83439</b> (1/8″)	Int Ex Sh Sa
Fluorescen	t	Mauve	<b>83433</b> (1/8″)	Sc Ho He Sc
Yellow	<b>83428</b> (1/8″)*			Fle Bre UV Min
Orange	<b>83430</b> (1/8″)			Ma
Dial	03 430 (4 (0))	WATC	CH VIDEONHERE	TE
Pink	<b>83429</b> (1/8")			Ac

Call 1.800.387.7439 or visit www.engraversdepot.ca

Please Note: Sheet Stock is supplied in full sheet sizes of 24% 48%. When ordering, use the individual part number located on the individual part number, a how to receive a full sheet size. To order a half sheet - 24% 24" add "-H" after the individual part number, and to order a quarter sheet - 12% 24" add "-H" after the individual part number. pre-applied to your sheet stock, include the following with your order. For "**Tinterior Use**" adhesive, add part number # 111111 to have a full sheet size of 24"x 48" applied, for a half sheet - 24"x 24" add"-H" and for a quarter sheet - 12"x 24" add"-Q". For "**Exterior Use**" adhesive, add part number # 233333 to have a full sheet size of 24"x 48" applied, for a half sheet - 24"x 24" add"-H" and for a quarter sheet - 12"x 24" add"-Q". For "**Exterior Use**" adhesive, add part number # 233333 to have a full sheet size of 24"x 48" applied, for a half sheet - 24"x 24" add"-H" and for a quarter sheet - 12"x 24" add"-Q". For "**Exterior Use**" adhesive, add part number # 333333 to have a full sheet size of 24"x 48" applied, for a half sheet - 24"x 24" add"-H" and for a quarter sheet - 12"x 24" add"-Q". Finited colours are for indication only and should not be used as a real material sample.

GRAVOTECH

# ENEFITS

- Laser engraving and cutting
- Glossy or frosted finish
- Excellent for clear signage
- Laser and rotary engravable
- Interior and exterior use

terior and exterior signage oplications...

# PECIFICATIONS

Finish	Gloss
Composition	Acrylic, 1-ply
Engraving Depth	.010"
Full Sheet	24" x 48"
Half Sheet	24" x 24" (add -H)
Quarter Sheet	12" x 24" (add -Q)
Other Size(s)	-

## APABILITIES

Interior	-
Exterior	-
Shear	.020"
Saw	•
Screen Print	•
Hot Stamp	-
Heat bending	-
Scratch resistant	-
Flexible	-
Break resistant	-
UV resistant	-
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

## ECH TIPS

crylic sheets can be engraved, paint filled, or used for cutouts. Another common use is to simply add thickness to an engraved sheet of metal or plastic. The added thickness has a strong presence on the wall.

23