

BENEFITS

- UV stable
- Excellent for interior and exterior signage
- A wide range of colors
- Matte finish
- Microthin surface layer for detailed engraving
- Reduce inventory with one material for rotary, laser, indoor and outdoor needs

APPLICATIONS

Architectural signage, industrial signage, labelling, legend plates...

SPECIFICATIONS

Finish	Matte
Composition	Acrylic
Engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	■
Saw	-
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	-
Flexible	■
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

The most versatile plastic material: indoor, outdoor, laser and rotary engraving and cutting. One product, one stock, many applications.

You can mix any surface and any core colors on demand.

For custom colors, see Custom materials on demand p.10.



Flexibility and performance for indoor and outdoor applications

Double-sided	2-ply			surface / core color	2-ply	surface / core color
	0.5 mm (.020")	0.8 mm (1/32")	1.3 mm (.050")			
Matte						
white / red				white / red	51006	70005
white / blue				white / blue	51011	
white / black				white / black	51017	49971
yellow / red				yellow / red	51007	70006
yellow / blue				yellow / blue	51012	
yellow / black				yellow / black	51018	49973
orange / white				orange / white	51035	51005
orange / black				orange / black	51020	51001
red / white				red / white	51034	49988
red / black				red / black		81585**
red / yellow				red / yellow	51055	51009
red / gold				red / gold	72304**	
						78586**
				burgundy / white	51043	49997
				burgundy / gold	51016	
				purple / white	67005*	67006*
						80771*

\*Subject to premature colorfading  
\*\* Sold in North America Only



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

