



Matte

	1-ply
clear	0.8 mm (1/32") 29918 1.6 mm (1/16") 29935 3.2 mm (1/8") 72083
extra white	29919 29936 31237
bright white*	78232
eggshell*	81351
newyork white*	81362
almond	29921
ivory*	81313
cream*	81355
candlewick*	81358
silver	29931
silver grey	29929 29946 32187
metallic blue*	81368
metallic grey*	81370
taupe*	81353
slate	29930

	1-ply
gold	0.8 mm (1/32") 29982 1.6 mm (1/16") 81363 3.2 mm (1/8")
copper*	81363
cocoa*	81311
brown*	81352
chocolate brown	29926 29943 31648
rust*	81365
pink*	81374
bordeaux*	81373
burgundy	29923 29939 31738
red	29922 29939 31700
yellow*	81281
burnt orange*	81360
orange*	81369
pine green	29927

	1-ply
green*	0.8 mm (1/32") 81359 1.6 mm (1/16") 81310 3.2 mm (1/8")
apple green*	81310
maui blue*	81372 45961
azure blue	29945 31406
patriot blue*	81371
navy blue*	81282
purple*	81354 78948
royal blue*	81361
black	29920 29937 31257
air force blue*	81312
light grey*	81364

	1-ply
clear*	0.8 mm (1/32") 75466 1.6 mm (1/16") 75459

Glossy/Matte

* Sold in North America Only
Available in other thicknesses. Please contact us.

The Gravotac™ process :



Adhere 0.8 mm (1/32") profile material to 1.6 mm (1/16") or 3.2 mm (1/8") substrate. Engrave using outline font. Peel excess profile material off substrate.

Call 1.800.387.3130 or visit www.engraversdepot.ca

Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.



BENEFITS

- Interior and exterior use
- Profile available with or without adhesive backing
- Cut with laser or rotary machines

APPLICATIONS

DDA & ADA compliant, tactile signage

SPECIFICATIONS

Finish	Matte or Glossy
Composition	Impact modified acrylic
Engraving depth	-
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	■
Break resistant	■
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

The ideal product for Braille and tactile signs cut with your laser machine. UV stable.
For custom thickness, please contact us.

