

BENEFITS

- Subsurface engraving
- 2 choices of surface: matte or gloss
- For indoor and outdoor use
- UV stable

APPLICATIONS

Indoor and outdoor signage,
professional plates, directories...

SPECIFICATIONS

Finish	Matte
Composition	DR Acrylic, 2-ply
Engraving Depth	.012"
Full Sheet	24" x 48"
Half Sheet	24" x 24" (add -H)
Quarter Sheet	12" x 24" (add -Q)
Other Size(s)	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Screen Print	■
Hot Stamp	■
Heat bending	■
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

UV stability for outdoor signage.
You can use Gravotech recommended
paint to colour any Gravoglas™
2-Plex™ subsurface engraving.
See p.77.



Rotary



UV Print



Indoor



Outdoor



Subsurface

Subsurface Engrave, Matte

Surface / Backing Colour

Clear / Clear	17941 (1/16") 18082 (1/8")
------------------	---

Clear / White	17947 (1/16") 18086 (1/8")
------------------	---

Clear / Eggshell	33982 (1/16")
---------------------	----------------------

Clear / Almond	17958 (1/16") 33977 (1/8")
-------------------	---

Clear / Cream	29658 (1/16")
------------------	----------------------

Clear / Yellow	17956 (1/16")
-------------------	----------------------

Clear / Red	17950 (1/16")
----------------	----------------------

Clear / Burgundy	18090 (1/8")
---------------------	---------------------

Clear / Azure Blue	17953 (1/16")
-----------------------	----------------------

Clear / American Blue	29663 (1/16")
--------------------------	----------------------

Clear / Royal Blue	29665 (1/16")
-----------------------	----------------------



Subsurface Engrave, Matte

Surface / Backing Colour

Clear / Chocolate Brown	17970 (1/16")
----------------------------	----------------------

Clear / Silver Grey	17961 (1/16") 34406 (1/8")
------------------------	---

Clear / Slate	29667 (1/16")
------------------	----------------------

Clear / Silver	29669 (1/16")
-------------------	----------------------

Clear / Black	17944 (1/16") 18084 (1/8")
------------------	---

