



Subsurface engraving Glossy

surface / backing color		2-ply		
		1.6 mm (1/16")	3.2 mm (1/8")	4.8 mm (.20")
clear / white		17988	18021	18101
clear / yellow		18003		
clear / red		17997		
clear / silver grey		29656		
clear / copper		17979		
clear / gold		17982	18091	
clear / black		17991	18024	18104

BENEFITS

- For indoor and outdoor use
- UV stable
- Subsurface engraving

APPLICATIONS

Indoor and outdoor signage, professional plates, directories

SPECIFICATIONS

Finish	Glossy
Composition	DR Acrylic
Engraving depth	0.3 mm (.012")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

UV stability for outdoor signage. You can use Gravograph recommended paint to color any Gravoglas™ 2-Plex™ subsurface engraving. See p.67.

For custom colors, see Custom materials on demand p.10.

Call 1.800.387.3130 or visit www.engraversdepot.ca

Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

